



Case study: Bracket for Electric forklift

CONVERSION SOLUTION

11-PCS WELDMENT TO ONE-PIECE INVESTMENT STEEL CASTING

Challenge

Interest for development of a stronger, lighter and more cost-efficient bracket component in alternative to the present 11 pieces welded component.

BEFORE: WELDMENT




Fabrication weight: 6,4 kg/pcs

Mechanical Properties for S 235 J2

ReH Yield strength (MPa): 235 N/mm2 Rm Tensile strength (MPa): 360 N/mm2

Weldment

Material Alloy Grade: S235J2 acc. to EN 10025-2







Case study: Bracket for Electric forklift

ENGINEERING SOLUTION

CARBON ALLOY STEEL CASTING

AFTER: CASTING



Casting weight: 5,1 kg/pcs

Mechanical Properties for G20Mn5 + N

ReH Yield strength (MPa): 300 N/mm2 Rm Tensile strength (MPa): 480 N/mm2

Castings Alloy


G20Mn5 + N Acc to Steel Casting standard EN 10293

Casting Method

Investment Casting (Water Glass Process)

Add Value

Finish machining







Case study: Bracket for Electric forklift

ENGINEERING OUTCOME

RESULT OF THE CONVERSION



- 20%

Weight Optimization

From 6,4 kg/pcs in Fabrication to 5,1 kg in Low Alloy Casted Steel.



Total Cost Reduction

Saving cost by redesign of shape, material & weight.



Strength Optimization

Improve material strength by changing the Steel Fabrication Alloy S235 JR to Low Alloy Casted Steel G 20Mn5 + N.






min. + 40%

Product Efficiency

WELD2CAST transformed a 11-pieces part into a onepiece Casting. The redesign simplified the assembly process for our client and reduced internal labour, manufacturing, inventory and overhead cost.

Combine Your Castings & Forgings with Our ADD-VALUE Services



Need assistance...

in determining if your welded part is a good candidate for a conversion to casting?





Surface Finishing